

## Kombi krāsns Metos LBET201



### Product information

---

SKU	4571342
Product name	Kombi krāsns Metos LBET201
Dimensions	960 × 825 × 1810 mm
Weight	330,000 kg
Jauda	20 x 1/1 GN
Tehniskā informācija	400 V, 60 A, 31,8 kW, 3NPE, 50 Hz, 65 dB CW: 3/4" Drain: ø 40 mm

### Description

Metos LBET201 combination oven with boiler has a clear control panel with shortcut and easy-to-select functions combined with easy cleaning of the oven and oven surfaces to facilitate and enhance the day-to-day operation of the kitchen. The precise temperature and humidity control of the oven chamber makes the food tasty, while retaining its color and texture, also allowing for frying and grilling.

The oven includes a trolley with 20 outlet pairs and outlet interval of 63 mm. The outlets can be used with GN1 / 1. The Metos LBET201 combination oven has three cooking modes: convection from + 30 ° C ... + 300 ° C, steam from + 30 ° C ... + 130 ° C and combined function + 30 ° C ... + 300 ° C. The oven has automatic system for measuring and controlling the humidity in the cooking chamber. All programs in the memory can be linked to shortcuts and create a favourite list.

The oven's structure is stainless steel. The smooth surfaces and watertight chamber, internal glass that fold to open make it easy to keep the device clean. Seven automatic wash programs are available as well as the automatic cleaning system LM. Calout descaling system that prevents the formation and build-up of limescale in the boiler.

The oven has an LCD-TFT color display for displaying favorite programs, preset programs, menus and settings. With the help of the scroller knob, it makes it easy to manage programs and select cooking stages. The double-glazed, left-handed door is equipped with heat-reflecting slotted glasses that, together with the air gap between the glasses, reduce heat radiation while retaining heat inside the unit, avoiding unnecessary energy loss. With USB connectivity, transferring HACCP data and cooking programs, as well as updating your operating system, is quick and easy.

- 20 rails trolley , rail distance 63 mm
- guides for GN1 / 1
- boiler model
- steam cooking + 30 °C to + 130 °C, convection air + 30 °C ... + 300 °C, combination function + 30 °C ... + 300 °C
- programmable with the ability to store cooking programmes in automatic sequence
- automatic temperature and humidity control system Clima®
- easy access to programmable user parameters
- Fast Dry® - System for quick dehumidification of the cooking chamber
- LED lighting in the oven chamber
- automatic reversing of the fan
- LCD-TFT color display
- Scroller Plus knob
- USB connection
- Temperature control at the product core using probe with 4 detection points.
- Core probe connection through a connector outside of the cooking chamber.
- door with double heat-reflective tempered glass with air gap
- internal glass folds open for easy cleaning
- left-handed door
- smooth watertight cooking chamber with rounded edges
- mechanical door switch
- 7 automatic cleaning programs
- IPX5 water protection

ACCESSORIES (ordered separately)

- hand shower
- needle-shaped cooking sensor
- energy optimisation system
- various cooking pots and dishes
- trolley for baking plates 600x400mm